

TECHNICAL DATA

TAMPER

BT 60, BT 65



Maximum reliability and longevity
All around engine protection




More transparency
Hour counter/tachometer with a service indicator which can be reset



Simple operation
Engine and fuel supply with combined switch

Shipping dimensions in cub.yd

BT 60	0.345
BT 65	0.345



Standard Equipment

- Engine Protection System
 - Protective engine covering
 - Paper air filter system with two stages
 - Automatic oil level control
 - Dual fuel filter system
- Vibration insulated steering bow
- Self-cleaning air filter housing
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- h-/ rpm meter
- 3-2-1 Warranty

Dimensions in inch

	B	H	L	L1	W
BT 60	13.8	40.6	28.7	13.2	9.1
BT 65	13.8	40.6	28.7	13.2	11.0

Optional Equipment

- Transport device with puncture proof wheels
- Tamper foot widths (6.3-13 in)
- Tamper foot extensions
- Special painting
- Tool kit
- Service Kit
- Operator protection contact breaker switch
- TOUGH WARRANTY

Technical Data

Weights

Operating weight CECE	lb	128	150
Basic weight	lb	126	148

Dimensions

Working width (tamper plate)	in	11.0	11.0
------------------------------------	----	------	------

Driving Characteristics

Working speed max.	ft/min	65.6	65.6
Area coverage max.	sq.ft/h	2,970.9	3,616.8

Drive

Engine manufacturer		Honda	Honda
Type		GXR 120	GXR 120
Emission stage		StageV/CARB P.3	StageV/CARB P.3
Cooling		air	air
Number of cylinders		1	1
Performance SAE J 1349	kW	2.8	2.8
Performance SAE J 1349	hp	3.8	3.8
Fuel		Gasoline	Gasoline
Drive system		mech.	mech.
Fuel comsump. aver. during operation	gal/h	0.2	0.2

Exciter system

Frequency	vpm	600.0-708.0	600.0-708.0
Impact force	lb	3,372	3,822

Capacities

Fuel	gal	0.8	0.8
------------	-----	-----	-----

Technical modifications reserved. Machines may be shown with options.

