

Technical sheet :

# ROOFER PLATFORM







## Benefits

- Cutting edge platforms designed for roof work.
- Secured platform.
- Non-slip metal flooring.
- Heavy duty and galvanised structure for an improved longevity.
- Platform NC: large 3,5 m working width.
- Roomy platform: can lift a pallet (Euro) even when folded.

## Technical characteristics







- Capacity from 365 to 1000 kg.
- Slewing platform +/- 90° on both sides.
- Safe: front opening only when a direct contact is made with the roof + can be moved only if the front part is closed.
- Legally approved for 3 persons
- Presence sensor forbidding any movement after door opening.
- Overload sensor.
- Physical sensor allowing door opening only if roof contact.

Technical characteristics		NC 365	NC 1000	PSR 2400 / 365 3P	PSR 2400 / 1000 3P
Distance to center of gravity (mm)		1493	1300	1493	1300
Capacities					
Capacity including people (kg)		365	1000	365	1000
Number of people		3	3	3	3
Weight and dimensions					
Overall length (mm)		l1 2920	2605	2920	2915
Overall height (mm)		h17 1614	1614	1954	1954
Width minimum (mm)		2420	2420	2420	2420
Width maximum (mm)		3682	3682	3682	3682
Depth (mm)		p5 1260	-	1260	-
Overall weight (kg)		1310	1210	1315	1215
Working Parameters					
Machine Equipment					
Rotation 1		180	180	180	180

Machines compatibility	NC 365	NC 1000	PSR 2400 / 365 3P	PSR 2400 / 1000 3P
Reference number	788789	788791	-	-
MT 1335 HA 75D ST5	X	-	-	-
MT 1335 HA 100D ST5	X	-	-	-
MT 1440 A	X	X	-	-
MT 1440 HA	X	X	-	-
MT 1840 A	X	X	-	-
MT 1840 HA	X	X	-	-
MT-X 1440 A	X	X	-	-
MT-X 1840 A	X	X	-	-
MRT 3255 Privilege Plus <b>OLD</b>	X	-	-	-
MRT-X 3255 Privilege Plus <b>OLD</b>	X	-	-	-
Reference number E-RECO	923309	921294	52719259	52719260
MRT 1645 75	X	X	X	X
MRT 1645 115	X	X	X	X
MRT 1845 75	X	X	X	X
MRT 1845 115	X	X	X	X
MRT 2145 115	X	X	X	X
MRT 2260 360 e	X	X	X	X
MRT 2260	X	X	X	X
MRT 2545 115	X	X	X	X
MRT 2570	X	X	X	X
MRT 2660 360 e	X	X	X	X
MRT 2660	X	X	X	X
MRT 3060	X	X	X	X
MRT 3570	X	X	X	X
MRT 3570 ES	X	X	X	X
MRT-X 1645	X	X	X	X
MRT-X 1845	X	X	X	X
MRT-X 2145	X	X	X	X
MRT-X 2260	X	X	X	X
MRT-X 2545	X	X	X	X
MRT-X 2570	X	X	X	X
MRT-X 2660	X	X	X	X
MRT-X 3060	X	X	X	X
MRT-X 3570	X	X	X	X
MRT-X 3570 ES	X	X	X	X
MRT 1640 Easy 3B S2 360° <b>OLD</b>	X	-	-	-
MRT 1640 Easy T4 S2 400° <b>OLD</b>	-	X	-	-
MRT 1840 Easy T4 S2 360° <b>OLD</b>	X	X	-	-
MRT 1840 Easy T4 S2 400° <b>OLD</b>	X	X	-	-
MRT 2145 Easy T4 S2 360° <b>OLD</b>	-	X	-	-
MRT 2145 Easy T4 S2 400° <b>OLD</b>	X	X	-	-
MRT 2150 Privilege Plus <b>OLD</b>	X	X	-	-
MRT 2470 Privilege Plus <b>OLD</b>	X	X	-	-
MRT 2545 Easy 3B S2 360° <b>OLD</b>	X	-	-	-
MRT 2545 Easy T4 S2 360° <b>OLD</b>	X	X	-	-
MRT 2545 Easy T4 S2 400° <b>OLD</b>	X	X	-	-
MRT 2550 Privilege Plus <b>OLD</b>	X	X	-	-
MRT 3050 Privilege Plus <b>OLD</b>	X	X	-	-
MRT 3255 Privilege Plus <b>OLD</b>	X	-	-	-
MRT-X 1440 Easy 400° <b>OLD</b>	X	X	-	-
MRT-X 1640 Easy 360° <b>OLD</b>	X	X	-	-
MRT-X 1640 Easy 400° <b>OLD</b>	X	X	-	-
MRT-X 1840 Easy 360° <b>OLD</b>	X	X	-	-
MRT-X 1840 Easy 400° <b>OLD</b>	X	X	-	-
MRT-X 2150 Privilege Plus <b>OLD</b>	X	X	-	-
MRT-X 2470 Privilege Plus <b>OLD</b>	X	X	-	-
MRT-X 2545 Easy 360° <b>OLD</b>	X	X	-	-

Machines compatibility	NC 365	NC 1000	PSR 2400 / 365 3P	PSR 2400 / 1000 3P
MRT-X 2545 Easy 400* <b>OLD</b>	X	X	-	-
MRT-X 2550 Privilege Plus <b>OLD</b>	X	X	-	-
MRT-X 3050 Privilege Plus <b>OLD</b>	X	X	-	-
MRT-X 3255 Privilege Plus <b>OLD</b>	X	-	-	-

**TABLE SYMBOL**

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes