Proven, reliable testing pump for pressure and tightness tests of piping systems and receptacles.

Testing and pressure range ≤ 6 MPa/60 bar/870 psi Water, oil, glycol

vvater, oii, giycoi	
pH-value of liquids	7–12
Temperature of liquids	≤ 60°C
Viscosity of liquids	≤ 1.5 mPa s

### **REMS Push – reliable pressure hold.**

#### Universal use

For plumbing, heating, solar system and sprinkler installations, for compressed air, steam and cooling systems, oil installations, for boiler and pressure vessel building.

# Design

Robust, job-site proven metal design for tough use. REMS Push with corrosion-resistant, powder-coated 12 ltr steel tank. Distortion resistant lever with ergonomic handle, doubles as carrying handle when locked. Wear resistant pressure piston in brass, Ø 30 mm. High-pressure hose with ½"-connection. Fine scale pressure gauge (accessory), p  $\leq$  1.6 MPa/16 bar/232 psi, for reading a pressure change of 0.01 MPa/0.1 bar/1.45 psi for tightness testing according to DIN 1988, as accessory.

# Stainless steel tank

REMS Push INOX with 12 ltr stainless steel tank. For extremely long life.

## **Functioning**

Pressure and tightness test with water or oil. Double valve system for reliable pressure built-up, with rust-proof steel balls. High pumping capacity with long stroke, fine pressure adjustment at short pushes. High pressure hose with fabric ply prevents measurement errors.





#### **Supply format**

**REMS Push.** Hand pressure testing pump with pressure gauge, p ≤ 6 MPa/ 60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi, Corrosion-resistant, powder-coated 12 ltr steel tank. 1.5 m high-pressure hose with ½"-connection. In a carton.

ArtNo.	
115000	



## **Supply format**

**REMS Push INOX.** Hand pressure testing pump with pressure gauge, p ≤ 6 MPa/60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi. 12 ltr stainless steel tank.

1.0 III liight procedure need with 72 Connection. In a carton.			
	ArtNo.		
	115001		



#### Accessories

Description	Pressure p ≤ MPa/bar/psi	ArtNo.	
Connecting piece with pressure gauge and shut off valve	6/60/870	115110	
•			
Fine scale pressure gauge	1.6/16/232	115045	



