

# Akumulatora naglotājs DCN660D2 bezogļīšu, 32-63mm, 18V / 2,0Ah, DeWalt

- Akumulatora veids: XR Li-Ion  
Voltāža: 18 V  
Akumulatora jauda: 2.0 Ah  
Naglu diametrs: 1,6 mm  
Naglu garums: 32 - 63 mm  
Aptveres leņķis: 20 °  
Aptveres naglu ietilpība 110 naglas  
Darba temperatūra: -20 līdz 50C  
Svars: 2,95 kg

Nav nepieciešama gāze, kas nodrošina ievērojami zemas ekspluatācijas izmaksas.

Divi ātrumi- vai jaudas līmeņi

Viegla naglu šaušanas dziļuma regulēšana.

Komplektācija:

2 x 2.0Ah XR Li-Ion akumulatori, Multi-voltāžas XR lādētājs

PVC koferis



# The DEWALT DCN660 XR Finishing Angled Nailer with Brushless Motor Technology.

The sequential operating mode allows for precision placement and the bump operating mode provides the user with production speed.

Increased visibility and durability along with protection for work-surface from the non-mar contact-trip and depths can be easily adjusted using the thumb wheel depth adjuster. Ergonomic tool design allows the nailer to fit easily between a 400mm centre stud. The user can engage the contact trip lock-off and prevent accidental dis-charge of fastener and dry fire lockout ensures that the tool is protected from firing without nails in the magazine.

Mechanical rather than gas operation offers consistent performance at temperature between -20 to 50°C and minimal cleaning/service requirements. Its cordless design allows you to work without the inconvenience and safety risk of trailing leads. Gas free operation offers a significant saving in running costs.

**\*\*\*Only for use with nails suitable for an Angled Nailer (sold seperately)\*\*\***

## Features and Benefits:

- Latest generation 18V XR Li-Ion Brushless 16Ga nailer offers the cutting edge in nailing technology
- BRUSHLESS motor offers runtime that cannot be beaten in a compact package
- Compact, lightweight and ergonomic design makes the tool easy and comfortable to use but durable enough for worksite environment
- Mechanical rather than gas operation offers low running costs and consistent performance at low temperatures
- Sequential mode allows for precision placement and the bump operating mode provides the user with production speed of up to 4 nails per second
- 2.0Ah XR battery packs offer compatability with all of your other 18V XR DEWALT Power Tools
- Depth of drive can be easily adjusted using the thumb wheel depth adjuster
- Tool free stall / jam clearance minimises down time
- Trigger and contact trip lock-off and prevent accidental dis-charge of fastener

## Technical Specification:

Battery chemistry - Li-Ion

Voltage - 18 V

Battery Capacity - 2.0 Ah

Nail Diameter - 1.6 (16Ga) mm

Magazine angle - 20 °

Magazine loading - Rear

Nail Length - 32 - 63 mm

Magazine capacity - 110 Nails

Length - 310 mm

Width - 95 mm

Height - 305 mm

Weight - 2.7 kg

Nailer Operating Mode - Bump and Sequential

Integrated Belt Hook - Yes

Jam Clearing - Tool free

Temperature Range - -20 to 50°C

Fault indicator - Yes

Noise L<sub>Pa</sub> 1sd / Uncertainty - 81 / 3 dB

Noise L<sub>Wa</sub> 1sd / Uncertainty - 92 / 3 dB

Vibration / Uncertainty - <2.5 / 1.5 m/s<sup>2</sup>