



TE 800-AVR : Built to blast !

Performance

Unmatched breaking performance thanks to exceptional impact energy : **21 J – 1890 impacts/min**

Dynamic hammering mechanism & unique robust **TE-S** connection end

Powerful **1850 W** motor

Robustness

Longer carbon brush

Highly robust and efficient HPD (High Performance Drive) with triple sealing chambers systems for longer service intervals and tool lifetime

Electronic power steering protects the tool against overload

Innovative cooling system

Comfort

Lowest vibrations values in its class thanks to Hilti's innovative Active Vibration Reduction (AVR) : **9 m/s² (2h30 permissible switched-on per day)**

"D-handle" design for perfect balance in **wall applications** and good handling in universal use

New back handle, wide and ergonomic for **floor demolition**



HI DRIVE
TECHNOLOGY

AVR



DRS-B provides a safer, cleaner, virtually dust-free environment by removing up to 97% of hazardous dust. Compatible with all TE-Y & TE-S Hilti's breakers

FLOOR

TE-SP wave chisels : Unique design, unique performance

Less sticking : "wave" design which create fewer points of contact between chisel and concrete

Self-sharpening : harder material inside (turning every 2 hours)

WALL

TE-SW wall chisels : The specialist for wall application !

Lighter : Easiest handling of the breaker and high comfort working

Shorter : High performance and precision



Floor demolition



Use with DRS-B



Opening



Renovation